

Gearboxes and Transmissions

Lubricants Catalogue



REPSOL

Let's invent the future





Index

1. Introduction	4
2. Manual transmissions	
Navigator MBT LL 75W-90	5
Navigator LL SAE 40	5
Navigator FE LL 75W-80	5
Navigator FE LL 75W-90	6
Navigator Transaxle 75W-80	6
Navigator GL-4 75W-80 and 80W-90	6
Navigator HQ GL-4 SAE 80W	7
Navigator HQ GL-4 75W-90	7
3. Automatic transmissions	
3.1. Passenger car transmissions	8
Automator ATF VI	8
Automator DCT	8
Automator CVT	9
Automator ATF Diafluid	9
3.2. Heavy duty vehicle transmissions	9
Automator ATF 14C	9
Automator ATF III	10
Automator ATF II	10
4. Differentials	
Navigator FE LL 75W-90	11
Navigator LL 80W-90	11
Navigator LL 85W-140	11
Navigator HQ GL-5 80W-90	12
Navigator HQ GL-5 85W-140	12
Navigator GL-5 80W-90 and 85W-140	12
Navigator HQ GL-5 SAE 90	12
4.1. Limited slip differentials	14
Navigator AWD LSD 75W-90	14
Navigator LSD 80W-90 and 85W-140	14
5. Other products	
Navigator GL-1 SAE 140 and 250	15
6. Transmissions for construction machinery	
Navigator TO-4 SAE 10W	16
Navigator TO-4 SAE 30	16
Navigator TO-4 SAE 50	16
7. Quality specifications	18
8. Repsol lubricant searcher	21
9. Packs	21
10. Commercial offices	23

1. Introduction

When you choose **Repsol**, you get so much more. Because you have the confidence from a top-level **global multi-energy company** present throughout the energy chain. We're a company that employs more than 24,000 people, and our products are sold in more than 80 countries, reaching 24 million customers. Our crude oil production exceeds 600,000 barrels of oil equivalent per day on average and has one of the most efficient refining systems in Europe.



**The Repsol Commitment
Net Zero Emissions
by 2050**

We manage low-emission power generation assets, including photovoltaic and wind energy projects. We are a large group in continuous transformation and diversification of businesses to **lead the energy transition**, being the first company from the sector to support the Kyoto Protocol, to issue a green bond, and to set the goal of achieving net zero emissions by 2050.


To achieve this goal, we are committed to technology and digitalization as fundamental pillars through a **model that integrates all technologies** for decarbonization, and is based on improved efficiency; renewable power generation; products with a low, neutral, or even negative carbon footprint; circular economy; and industrial innovation. That is what has made us leaders in innovation, sustainability, and efficiency, thanks to our cutting-edge projects.





To align ourselves with our goal of zero emissions and to adapt ourselves to the needs of our customers, **we have restructured the lubricant ranges.**



2. Manual transmissions

Navigator MBT LL 75W-90		
	<p>Synthetic fluid certified by Mercedes-Benz [MB 235.11] for use in manual and automatic transmissions of its more modern vehicles (Actros, etc.).</p> <p>This 100% synthetic oil helps lower fuel consumption and allows for extended oil change intervals. Because it reduces mechanical loss, it also helps reduce temperatures - even in gearboxes without oil coolers working in harsh conditions, protecting and increasing the lifespan of gearbox parts.</p>	
QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS	API GL-4 MAN 341 TYPE MB	MB-APPROVAL 235.11* *Formal approval

Navigator LL SAE 40			
	<p>This synthetic fluid is designed to lower fuel consumption, extend oil change intervals, and handle severe conditions in manual, hybrid, and automatic transmissions of heavy vehicles.</p> <p>Navigator LL SAE 40 is certified by EATON as PS-386 for use in new gearboxes such as Fuller Advantage, Ultrashift, Ultrashift PLUS, Freightliner M2, Cascadia, New Cascadia, Coronado, Kenworth [T, W, and off highway series], Thomas Built Buses, and models with up to 18 gears (FO, FM, FS, RT, FR series) as well as hybrid vehicles (EH and EHV series).</p> <p>This new lubricant is approved for use in older EATON models requiring PS-164 Rev. 7 fluid.</p>		
QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS	API MT-1 EATON PS-386* EATON PS-164 REV. 7 (obsolete)	MACK TO-A PLUS MERITOR O-81 NAVISTAR MPAPS B-6816 TYPE II	*Formal approval

Navigator FE LL 75W-80			
	<p>Synthetic lubricant especially designed to meet the lubrication requirements of leading vehicle manufacturers for manual gearboxes which require extended oil change intervals. It contributes to fuel savings and allows for smooth shifting, even at low temperatures.</p>		
QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS	API GL-4 DAF TRANSMISSIONS EATON EUROPE IVECO TRANSMISSIONS	MAN 341 Z-4* MAN 341 E-3 (obsolete) RENAULT [B0032/2 ANNEX 3] VOLVO 97305	ZF TE-ML 01L/02L/08/16K* *Formal approval

Navigator FE LL 75W-90



Synthetic lubricant designed to lubricate differentials and certain gearboxes and transmissions in vehicles, making it possible to unify both systems using a single oil. It provides unbeatable performance in the drive axles and rear axles of heavy duty vehicles thanks to its ability to withstand heavy loads and its exceptional fluidity at low temperatures. It contributes to fuel savings and allows drain intervals to be increased.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

API GL-4/GL-5/MT-1
ARVIN MERITOR 0-76-N

DAF API GL-5 & TRANSMISSIONS
IVECO AXLES & TRANSMISSIONS
MACK GO-J
MAN 341 Z2, 342 S1*
(old MAN 3343)
MB 235.0

MB-APPROVAL 235.8*
MIL-PRF-2105E
RENAULT AXLES
SAE J 2360*
SCANIA STO 2:0 A FS/STO 1:0*
VOLVO 97312*

ZF TE-ML 02B/05A/12L/12N
/16F/17B/19C/21A*
*Formal approval

Navigator Transaxle 75W-80



Synthetic lubricant for manual gearboxes and transaxle differentials of cars which require an API GL-4+ quality level and work in a wide range of temperatures. This oil has been especially designed to meet the lubrication requirements established by leading vehicle manufacturers (Peugeot, Citroën, Renault, General Motors, etc.) for their manual gearboxes and differentials.

QUALITY LEVELS

API GL-4
BMW MTF LT-2
FIAT MZ6
GM 1940764, 1940768

HONDA MTF, MTF-II, MTF-III
NISSAN MT-XZ
PSA B71 2330
TRANSELF NFJ, NFP

TRANSELF TRJ, TRT, TRZ
VOLVO 97308, 97309
VW G 009 317

Navigator GL-4 75W-80 and 80W-90



Lubricant for manual gearboxes of commercial vehicles and cars in which an API GL-4 quality level is required. This oil has been especially designed to meet the lubrication requirements established by leading vehicle manufacturers for their manual gearboxes.

QUALITY LEVELS

API GL-4

Navigator HQ GL-4 SAE 80W



Monograde lubricant oil for manual gearboxes in which an API GL-4 quality level is required.

QUALITY LEVELS,
APPROVALS AND
RECOMMENDATIONS

API GL-4
DAF TRANSMISSIONS
IVECO 18-1807 MGS2

MB 235.1*
RENAULT TRANSMISSIONS
VW 726

ZF TE-ML 08/17A*
*Formal approval

Navigator HQ GL-4 75W-90



Multi-grade lubricant oil for the lubrication of manual gearboxes and transmission mechanisms in which an API GL-4 quality level is required. The oil viscosity allows it to be used at a wide range of vehicle start-up temperatures.

QUALITY LEVELS


API GL-4
DAF TRANSMISSIONS
IVECO TRANSMISSIONS


MIL-L-2105
ZF TE-ML 08



3. Automatic transmissions

3.1. Passenger car transmissions

Automator ATF VI		
	<p>Automator ATF VI is a low-viscosity synthetic lubricant approved by General Motors for use in all its automatic transmissions. It complies with the DEXRON III, DEXRON II and TASA specifications. It is recommended for passenger cars and certain heavy duty vehicles.</p>	
<p>QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS</p> <p>AISIN WARNER JWS 3309 (T-IV) & JWS 3324 (WS), AW-1 AUDI 5 HP LT71141 BMW ETL-8072B BMW JWS 3309 (T-IV) BMW LA2634 BMW LT 71141 (ZF 5 HP 18FL/19FL/24A) CHRYSLER/DODGE MOPAR AS 68 RC (T-IV), JWS 3309 FIAT T-IV TYPE, JWS 3309 FORD FNR5 (MAZDA M5, XT-9-QMM5) FORD MERCON LV FORD WSS-M2C-938-A / XT-10 QLV GM DEXRON VI* HONDA ATF-Z1 [except in CVTS] HONDA DW-1 HYUNDAI/KIA SP-III, SP-IV HYUNDAI/KIA SP-IV M (SP4-M)</p>	<p>HYUNDAI/KIA SP-IV-RR ISUZU BESCO ATF-II, ATF-III, ATF SP JAGUAR ATF 3403-M115 JAGUAR ATF LT71141, ZF 5HP24 JAGUAR ATF 3403, JLM20238 JASO M315 1A-LV MAZDA ATF M-III, M-V MITSUBISHI DIAQUEEN SK, SP-II, SP-III MITSUBISHI DIAQUEEN ATF-MA1, ATF PA NISSAN MATIC FLUID C, D, J, K, S OPEL/GM 19 40 700 / 767 OPEL/GM 21005966 TRANSAXLE OPEL/GM 22 17466 OPEL/GM 88900925 OPEL/GM 9986195 PEUGEOT/CITROEN (PSA) AL4 PEUGEOT ZF 4HP20 AUTOMATIC GEARBOX OIL (#9730.AE) PORSCHE ATF 3403-M115, PORSCHE T-IV (JWS 3309) PORSCHE ZF 5HP19FL, ZF 5HP20, LT71141 SAAB 93 165 147</p>	<p>SAAB T-IV (JWS 3309) SUBARU ATF 5AT SUBARU ATF, ATF HP SUZUKI ATF 2326 TOYOTA ATF D-II, D-III TOYOTA ATF T-III, T-IV TOYOTA ATF WS VOLVO CE 97340 VW 5HP (18FL, 30) VW 5HP (19FL, 24A) VW 5HP (ZF 5 HP 30) VW G 055 025 A2 (JWS 3309) VW G 055 162-A2, A6 (ZF LIFEGUARD FLUID 6 PLUS) VW G 060 162- A2 (ZF LIFEGUARD FLUID 8) VW G 052 162 (ZF LIFEGUARD FLUID 5) VW TL 521 62 ZF 8 SPEED TRANSMISSIONS ZF 9 SPEED TRANSMISSIONS ZF TE-ML 05L, 09, 11A, 11B, 21L *Formal approval</p>

Automator DCT		
	<p>Synthetic lubricant for DCT or DSG (dual-clutch gearbox) automatic transmissions, which provides users with faster, smoother gear shifting and helps to reduce fuel consumption. This oil has been designed for use in the transmissions of leading passenger car manufacturers such as Volkswagen, Ford, Mercedes-Benz, etc.</p>	
<p>QUALITY LEVELS</p> <p>BMW 83 22 2 148 578 / 83 22 2 148 579 / 83 22 0 440 214 / 83 22 2 147 477</p>	<p>FORD WSS-M2C-936-A MB 236.21 / 236.24 / 236.25 MITSUBISHI SSTF-I PSA 9734.S2</p>	<p>PORSCHE 999.917.080.00 VOLVO 1161838, 1161839 VW TL 052 182 / TL 052 529</p>

Automator CVT



Long-lasting synthetic lubricant for latest-generation continuously variable transmissions (CVTs), either belt or chain driven. It is primarily recommended for Asian vehicles.

QUALITY LEVELS

AUDI MULTITRONIC
CHRYSLER / JEEP / DODGE NS-2 / CVT +4
DAIHATSU AMMIX CVT / CVTF / TC
HONDA HMMF / HCF2

HYUNDAI / KIA CVT-J1 / SP-III
JASO M315 1A
MAZDA JWS 3320
MINI COOPER EZL 799 / 799AVW G 052
516 / G 052 180 A2
MITSUBISHI SP-III / CVTF-J1 / J4 / J4+

NISSAN NS-1 / NS-2 / NS-3
SUBARU ECVT / ICVT / FG / NS-2
SUZUKI CVTF / NS-2 / CVT GREEN 1 & 2
TOYOTA CVTF TC /CVTF FE

Automator ATF Diafluid



Synthetic-technology lubricant oil for automatic transmissions and power-assisted steering, especially designed to meet the needs of most Asian car manufacturers (Mitsubishi, Suzuki, Toyota, Nissan, Honda and Subaru, among others). It can also be used in continuously variable transmissions (CVTs) in which the manufacturer allows the use of an automatic transmission fluid (ATF).

QUALITY LEVELS

ALLISON C-4, TES 295, TES 389
DEXRON III H

FORD MERCON V
MAN 339 V2/339 Z2, Z11/339 L1
MB-APPROVAL 236.9
VOITH H55.6336

ZF TE-ML 03D/04D/14B/17C/20B/25B
T-II/T-IV

3.2. Heavy duty vehicle transmissions

Automator ATF 14C



Synthetic fluid for automatic transmissions in industrial vehicles and buses requiring long drain intervals or severe driving conditions. Certified for use by major transmission manufacturers. Approved for use in ZF EcoLife, ZF Ecomat, and Voith Diwa transmissions.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

MAN 339 TYPE V1/ Z3/ Z12*
MB 236.9*
VOITH H55.6336XX / 150.014524.XX*
VOLVO 97341*

ZF TE-ML 04D/ 14C/ 16M/ 16S/ 20C
[APPROVAL NUMBER ZF003586]*
*Formal approval

Automator ATF III



Long-lasting synthetic lubricant for automatic transmissions which can be used in passenger cars, commercial vehicles and construction machinery. It is recommended for transmissions and power steering that require a fluid which complies with the DEXRON III specification. Automator ATF III has also been especially designed to meet the most stringent requirements of automatic gearboxes in heavy duty vehicles which require the Allison TES-295 specification. It meets the requirements of Voith and other manufacturers.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

ALLISON C-4
ALLISON TES 295, TES 389
FORD MERCON V
GM DEXRON III H
MAN 339 V-2 / 339 Z-2, Z-11 / 339 L-1*

MB 236.9*
VOITH 55.6336*
VOLVO TRANSMISSION OIL 97341*, AT101
ZF TE-ML 03D/04D/14B/17C/20B/25B*
*Formal approval

Automator ATF II



Special oil for automatic transmissions (ATF) which meets the demands of manufacturers requiring the DEXRON II D quality level. It is especially recommended for automatic transmissions and power steering in vehicles, and may also be used in torque converters, hydraulic systems and other applications in which an ATF DEXRON II fluid is required.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

ALLISON C-4

FORD MERCON
GM DEXRON II D
MAN 339 V-1/339 Z-1/339 L-2*
MB 236.9*
VOITH H55.6335*

VOLVO 97341*
ZF TE-ML 03D/04D/11A/14A/17C*
*Formal approval



4. Differentials

Navigator FE LL 75W-90



Synthetic lubricant designed for differentials and some vehicle's gearboxes and transmissions: a single oil that can be used in both systems. It provides unbeatable performance in rear drive axles of heavy vehicles thanks to its ability to support heavy loads and its exceptional fluidity at low temperatures. It contributes to lower fuel consumption and allows for extended oil change intervals.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

API GL-4/GL-5/MT-1
ARVIN MERITOR 0-76-N

DAF API GL-5 &
TRANSMISSIONS
IVECO AXLES & TRANSMISSIONS
MACK GO-J
MAN 341 Z2, 342 S1* (old MAN
3343)

MB 235.0
MB-APPROVAL 235.8*
MIL-PRF-2105E
RENAULT AXLES
SAE J 2360*
SCANIA STO 2:0 A FS/STO 1:0*

VOLVO 97312*
ZF TE-ML 02B, 05A, 05B
(obsolete), 07A, 08, 12L, 12N,
16F, 17B, 19C AND 21A*
*Formal approval

Navigator LL 80W-90



Long-lasting oil for differentials and certain manual gearboxes that require a GL-5 quality level. It is particularly recommended for differentials in commercial and off-road vehicles working under harsh conditions that require a high-performance lubricant. It complies with current manufacturers' specifications that require oils with long drain intervals which can double or even triple the time between oil changes in comparison with conventional mineral oils.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

API GL-5/MT-1
ARVIN MERITOR 076-D

DAF API GL-5
IVECO AXLE
MACK GO-J
MAN 342 M3 AND 341 GA1*
MB 235.20*
RENAULT AXLE

SAE J 2360
SCANIA STO 1:0 for gearboxes*
VOLVO 97310
ZF TE-ML
05A/07A/08/12L/12M/16B/17B/19B/21A*
*Formal approval

Navigator LL 85W-140



Long-lasting oil for differentials and certain manual gearboxes that require a GL-5 quality level. It is particularly recommended for differentials in commercial and off-road vehicles working under harsh conditions that require a high-performance lubricant. It complies with current manufacturers' specifications that require oils with long drain intervals which can double or even triple the time between oil changes in comparison with conventional mineral oils.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

API GL-5/MT-1
ARVIN MERITOR 076-A
DAF API GL-5
IVECO AXLE

MACK GO-J
SCANIA STO 1:0 for gearboxes*
SCANIA STO 1:0 for
differentials*

VOLVO 97310
ZF TE-ML
05A/07A/08/12M/16D/21A*
*Formal approval

Navigator HQ GL-5 80W-90



Multi-grade extreme pressure lubricant oil, used in automotive differentials or transmissions groups and in manual gearboxes in which API GL-5 oil is required. It is especially recommended for hypoid differentials due to its high load capacity. This oil was specially designed to comply with the lubrication requirements established by leading manufacturers.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

API GL-5
DAF API GL-5
MAN 342 M1
MB 235.0*
MIL-L-2105 D

RENAULT AXLES
VOITH TURBO 132.00374400
[EX 3.325-339]*
ZF TE-ML 07A/08/16B/16C/17B/19B/21A*
*Formal approval

Navigator HQ GL-5 85W-140



Multi-grade extreme pressure lubricant oil specially developed for use in differentials or transmission units and manual gearboxes in which API GL-5 oil is required. Its high load capacity means that it is particularly recommended for hypoid differentials.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

API GL-5
DAF API GL-5
MIL-L-2105 D

VOLVO 97310
ZF TE-ML 07A/08/16C/16D/21A*
*Formal approval

Navigator GL-5 80W-90 and 85W-140



Multi-grade extreme pressure lubricant oil specially developed for use in differentials or hypoid and helical transmission units in which API GL-5 quality is required.

QUALITY LEVELS

API GL-5

Navigator HQ GL-5 SAE 90



Monograde lubricant oil with extreme pressure additives, recommended for use in differentials and rear drive axles of vehicles or hypoid transmission units. It can also be used in gearboxes and other gears, especially in industrial vehicles working under very harsh service conditions, at low speeds and high loads.

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

API GL-5
MAN 342 M1
MB 235.0*
VOLVO 97310

VW 727
ZF TE ML-
05A/07A/08/16B/16C/17B/19B/21A*
*Formal approval



4.1 Limited slip differentials

Navigator AWD LSD 75W-90



Synthetic multi-grade lubricant oil recommended for locking transmission systems or limited slip differential (LSD) units commonly used in construction machinery and all-terrain vehicles with several drive axles.

**QUALITY LEVELS,
APPROVALS AND
RECOMMENDATIONS**

API GL-5, LSD

Navigator LSD 80W-90 and 85W-140



Multi-grade lubricant oil for locking differentials in commercial vehicles, construction machinery vehicles and, in general, four-wheel drive vehicles in which fluids with limited slip differential (LSD) characteristics are required. It can also be used in non-locking differentials in which an extreme pressure, API GL-5 quality level lubricant is required.

**QUALITY LEVELS,
APPROVALS AND
RECOMMENDATIONS**

API GL-5
ZF TE-ML 05C/07A/08/12C/21C (80W-90)*

*Formal approval

5. Other products

Navigator GL-1 SAE 140 and 250



Monograde lubricant oil produced using highly refined mineral base oils. It may be used in manual transmissions and other gear mechanisms which, due to their design and load, operate under low or moderately demanding working conditions.

QUALITY LEVELS

API GL-1



6. Transmissions for construction machinery

Navigator TO-4 SAE 10W



Lubricant oil for construction machinery, especially formulated to meet the requirements of the CATERPILLAR, ALLISON and KOMATSU specifications, used in automatic transmissions, clutches and brakes, as well as in final drives, hydraulic systems, crown gears and differentials [according to SAE grade].

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

ALLISON C-4
CATERPILLAR TO-4
KOMATSU KES 07.868.1*

ZF TE-ML 03C, APPROVAL ZF003469*
*Formal approval

Navigator TO-4 SAE 30



Lubricant oil for construction machinery, especially formulated to meet the requirements of the CATERPILLAR, ALLISON and KOMATSU specifications, used in automatic transmissions, clutches and brakes, as well as in final drives, hydraulic systems, crown gears and differentials [according to SAE grade].

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

ALLISON C-4
API CF
API GL-4
CATERPILLAR TO-4

KOMATSU KES 07.868.1*
ZF TE-ML 03C, 07F, APPROVAL
ZF003472*
*Formal approval

Navigator TO-4 SAE 50




Lubricant oil for construction machinery, especially formulated to meet the requirements of the CATERPILLAR, ALLISON and KOMATSU specifications, used in automatic transmissions, clutches and brakes, as well as in final drives, hydraulic systems, crown gears and differentials [according to SAE grade].

QUALITY LEVELS, APPROVALS AND RECOMMENDATIONS

API CF
API GL-4
CATERPILLAR TO-4

KOMATSU KES 07.868.1*
*Formal approval



7. Quality specifications

MANUAL TRANSMISSIONS

PRODUCT	Navigator MBT LL 75W-90	Navigator FE LL 75W-90	Navigator LL SAE 40	Navigator FE LL 75W-80	Navigator Transaxle 75W-80	Navigator GL-4 75W-80	Navigator GL-4 80W-90	Navigator HQ GL-4 SAE 80W	Navigator HQ GL-4 75W-90
API	GL-4	GL-4 / GL-5 /MT-1	MT-1	GL-4	GL-4	GL-4	GL-4	GL-4	GL-4
ARVIN MERITOR		076-N							
BMW					MTF LT-2				
DAF		API GL-5 & Transmissions		Transmissions				Transmissions	Transmissions
EATON FULLER			PS-386*						
FIAT					MZ6I				
GM					1940764, 1940768				
HONDA					MTF, MTF-II, MTF-III				
IVECO		Axles & Transmissions		Transmissions				Transmissions	
MACK		GO-J	TO-A Plus						
MAN	341 Type MB	341 Z2 / 342 S1*		341 Z4*					
MB	235.11*	235.0 [level] / 235.8*						235.1*	
MERITOR			O-81						
MIL		PRF-2105 E							L-2105
NAVISTAR			MPAPS B-6816 Type II						
NISSAN					MTF, MTF-II, MTF-III				
PSA					B71 2330				
RENAULT		Axles							
SAE		J 2360							
SCANIA		STO 2:0 A FS / STO 1:0*							
VOITH									
VOLVO		97312*		97305	97308, 97309				
VW								726	
ZF TE-ML	MT-1	02B / 05A / 12L / 12N / 16F / 17B / 19C / 21A*		01L / 02L / 08 / 16K*				08 / 17A*	08

*Formal approval

AUTOMATIC TRANSMISSIONS

PRODUCT	Automator ATF 14C	Automator ATF VI	Automator ATF III	Automator ATF Diafluid	Automator DCT	Automator CVT	Automator ATF II
ALLISON			C-4/TES 295/TES 389	C-4			C-4
BMW		JWS 3309 (T-IV), LA2634 and ETL-8072B			83 22 2 148 578 / 83 22 2 148 579 / 83 22 0 440 214 / 83 22 2 147 477		
CHRYSLER		MOPAR AS 68 RC (T-IV) and JWS 3309		ATF +3/+4		NS-2	
DAIHATSU				AMMIX ATF D-II/D-III MULTI		Ammix CVT / CVTF / TC	
DEXRON		VI*	III H	III H			II D
FORD		MERCON LV WSS-M2C-938-A / XT-10 QLV	MERCON V	MERCON	WSS-M2C-936-A		MERCON
HONDA		ATF-Z1 (except in CVTs) and DW-1		Z-1/CVT		HMMF/HCF2	
HYUNDAI		SP-IV, SP-IV M (SP4-M), SP-IV-RR and SP-III				CVT-J1 / SP-III	
JASO		M315 1A-LV		M315-2004 CLASS 1A-03		M315 1A	
MAN	339 Type V1 / Z3 / Z12*		339 V2 / 339 Z2, Z11 / 339 L1*				339 V1/339 Z1/339 L2*
MAZDA		ATF M-III and ATF M-V				JWS 3320	
MB	236.9*		236.9*		236.21 / 236.24 / 236.25		236.9*
MITSUBISHI		DIAQUEEN ATF-MA1, ATF PA DIAQUEEN SK, SP-II and SP-III		SP-II/SP-III / CVT	SSTF-I	SP-III / CVTF-J1 / J4 / J4+	
NISSAN		MATIC FLUID C, D, J, K, and S		MATIC-D/J/K/CVT		NS-1/NS-2/NS-3	
OPEL/GM		19 40 700 / 767, 21005966 Transaxle, 22 17466, 88900925, 9986195					
SUBARU		ATF, ATF 5AT and ATF HP		ATF Matic J/CVT [ECVTF]		ECVT / iCVT / FG / NS-2	
SUZUKI		ATF 2326		ATF 3317		CVTF / NS-2 / CVT Green 1 & 2	
TOYOTA		ATF D-II, D-III, T-III, T-IV and WS		T-II/T-IV		CVTF TC/CVTF FE	
VOITH	H55.6336xx / 150.014524.xx*		H55.6336 ^h				H55.6335*
VOLVO	97341-073*	CE 97340	Transmission Oil 97341*, AT101		1161838 1161839		97341*
VW		5 HP (ZF 5 HP 30), 5 HP (18 FL, 30), 5 HP (19FL, 24A), G 052 162 [ZF Lifeguardfluid 5] and TL 521 62			TL 052 182/TL 052 529	G 052 516 / G 052 180 A2	
ZF TE-ML	04D / 14C / 16M / 16S / 20C / 25C*	5L, 09, 11A, 11B, 21L	03D/04D / 14B / 17C / 20B/25B*				03D / 04D / 11A / 14A / 17C*

DIFFERENTIALS

PRODUCT	Navigator FE LL 75W-90	Navigator LL 80W-90	Navigator LL 85W-140	Navigator HQ GL-5 80W-90	Navigator HQ GL-5 85W-140	Navigator GL-5 80W-90 and 85W-140	Navigator HQ GL-5 SAE 90
API	GL-4 / GL-5 / MT-1	GL-5 / MT-1	GL-5 / MT-1	GL-5	GL-5	GL-5	GL-5
ARVIN MERITOR	076-N	076-D	076-A				
DAF	API GL-5 & Transmissions	API GL-5	API GL-5	API GL-5	API GL-5		
IVECO	Axles & Transmissions		Transmissions				Transmissions
MACK	GO-J	GO-J	GO-J				
MAN	341 Z2 / 342 S1*	342 M3 / 341 GA1*		342 M1			342 M1
MB	235.0 [level] / 235.8*	235.20*		235.0*			235.0*
MIL	PRF-2105 E			L-2105 D	L-2105 D		
RENAULT	Axles	Axles		Axles			
SAE	J 2360*	J 2360					
SCANIA	STO 2:0 A FS / STO 1:0*	STO 1:0*	STO 1:0*				
VOITH				Turbo 132.00374400 [formerly 3.325-339]*			
VOLVO	97312*	97310	97310		97310		97310
VW							727
ZF TE-ML	02B / 05A / 12L / 12N / 16F / 17B / 19C / 21A*	05A / 07A / 08 / 12L / 12M / 16B / 17B / 19B / 21A*	05A / 12M / 16D / 21A*	07A / 08 / 16B / 16C / 17B / 19B / 21A*	07A / 08 / 16C / 16D / 21A*		07A / 08 / 16B / 16C / 17B / 19B / 21A*

LIMITED SLIP DIFFERENTIALS

PRODUCT	Navigator AWD LSD 75W-90	Navigator LSD 80W-90	Navigator LSD 85W-140
API	GL-5	GL-5	GL-5
MIL		L-2105-D	
ZF TE-ML		05C / 07A / 08 / 12C / 21C*	

OTHER PRODUCTS

PRODUCT	Navigator GL-1 SAE 140	Navigator GL-1 SAE 250
API	GL-1	GL-1

*Formal approval

TRANSMISSIONS FOR CONSTRUCTION MACHINERY

PRODUCT	Navigator TO-4 SAE 10W	Navigator TO-4 SAE 30	Navigator TO-4 SAE 50
ALLISON	C-4	C-4	
API		GL-4/CF	GL-4/CF
CATERPULAR	CAT TO-4	CAT TO-4	CAT TO-4
KOMATSU	KES 07.868.1*	KES 07.868.1*	KES 07.868.1*
ZF TE-ML	03C*	03C/07F*	

8. Repsol Lubricant Searcher



Access the **Repsol Lubricant Searcher** and find the perfect lubricant for your vehicle.



Scan this QR code

9. Packs

MANUAL TRANSMISSIONS

PRODUCT	BULK	1000 L CONTAINER	208 L DRUM	20 L DRUM	5 L PACK	4 L PACK	1 L PACK
NAVIGATOR MBT LL 75W-90				✓			
NAVIGATOR FE LL 75W-90		✓	✓	✓			✓
NAVIGATOR LL SAE 40				✓			
NAVIGATOR FE LL 75W-80		✓	✓	✓			✓
NAVIGATOR TRANSAXLE 75W-80	✓			✓			✓
NAVIGATOR GL-4 75W-80			✓	✓			✓
NAVIGATOR GL-4 80W-90						✓	
NAVIGATOR HQ GL-4 SAE 80W			✓		✓		
NAVIGATOR HQ GL-4 75W-90			✓	✓	✓		✓

AUTOMATIC TRANSMISSIONS

PRODUCT	BULK	1000 L CONTAINER	208 L DRUM	20 L DRUM	5 L PACK	4 L PACK	1 L PACK
AUTOMATOR ATF II		✓	✓	✓	✓		✓
AUTOMATOR ATF III		✓	✓	✓	✓		✓
AUTOMATOR ATF VI				✓			✓
AUTOMATOR CVT		✓		✓	✓		✓
AUTOMATOR ATF DIAFLUID		✓	✓	✓	✓		✓
AUTOMATOR DCT		✓		✓			✓
AUTOMATOR ATF 14C			✓				

DIFFERENTIALS

PRODUCT	BULK	1000 L CONTAINER	208 L DRUM	20 L DRUM	5 L PACK	4 L PACK	1 L PACK
NAVIGATOR HQ GL-5 SAE 90	✓	✓	✓	✓	✓		
NAVIGATOR FE LL 75W-90		✓	✓	✓			✓
NAVIGATOR LL 80W-90			✓				
NAVIGATOR LL 85W-140		✓	✓				
NAVIGATOR HQ GL-5 80W-90	✓	✓	✓	✓	✓		✓
NAVIGATOR HQ GL-5 85W-140		✓	✓	✓	✓		✓
NAVIGATOR GL-5 80W-90			✓	✓			✓

LIMITED SLIP DIFFERENTIALS

PRODUCT	BULK	1000 L CONTAINER	208 L DRUM	20 L DRUM	5 L PACK	4 L PACK	1 L PACK
NAVIGATOR LSD 80W-90			✓	✓	✓		
NAVIGATOR AWD LSD 75W-90							✓
NAVIGATOR LSD 85W-140							✓

OTHER PRODUCTS

PRODUCT	BULK	1000 L CONTAINER	208 L DRUM	20 L DRUM	5 L PACK	4 L PACK	1 L PACK
NAVIGATOR GL-1 SAE 140				✓			
NAVIGATOR GL-1 SAE 250				✓			

TRANSMISSIONS FOR CONSTRUCTION MACHINERY

PRODUCT	BULK	1000 L CONTAINER	208 L DRUM	20 L DRUM	5 L PACK	4 L PACK	1 L PACK
NAVIGATOR TO-4 SAE 10W		✓	✓	✓			
NAVIGATOR TO-4 SAE 30		✓	✓	✓			
NAVIGATOR TO-4 SAE 50	✓	✓	✓	✓			

10. Commercial offices



Headquarters

c/ Méndez Álvaro, 44.
28045 Madrid, España
Tel: 901 111 999.
lubricantes@repsol.com



France

Laetitia Lecomte
Tel: [+33] 1 46 96 65 23
Mob: [+33] 1 46 96 65 23
Fax: [+33] 1 46 96 66 42
laetitia.lecomte@repsol.com



Asia-Pacific

Víctor Velázquez López
10 Marina Boulevard, #14-01
Marina Bay Financial Centre Tower 2
Singapore 018983
Tel: [+65] 6808 1065
vvelazquezl@repsol.com



Peru

Víctor Rivera Bernuy
Av. Víctor Andrés Belaúnde, 147
Edif. Real 5, Piso 3, San Isidro, Lima, Perú
Tel: [+51] 215-6225
Cel: [+51] 939239060
Fax: [+51] 421-8591
v.rivera@repsol.com



Brazil

Silvio Frasson
Rua Leopoldo Couto de Magalhães Júnior, 758
11º andar, escritórios 111 e 112, Itaim Bibi
04542-000 São Paulo, Brasil
Tel: [+55] 21-25597200
silvio.frasson@repsol.com



Portugal

João Vasques
Av. José Malhoa nº 16 B, 8º
1099-091 Lisboa, Portugal
Tel: [+351] 213 119 000
sac.rlesa@repsol.com





REPSOL

Let's invent the future